


DPM 348

Dowcor 1

DOUGLAS AIRCRAFT COMPANY
ATTN R. R. LALLY
3855 LAKEWOOD BLVD.
INTERNAL MAIL CODE 126-14
LONG BEACH, CA 90846



DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

MATL NAME: MOLYKOTE(R) 33 GREASE - LIGHT
EMERGENCY TELEPHONE NO. (517) 496-5900

SECTION I - GENERAL INFORMATION

MANUFACTURERS NAME: DOW CORNING CORPORATION
ADDRESS: SOUTH SAGINAW ROAD, MIDLAND MI 48686

PROPER SHIPPING NAME(49CFR 172.101): NONE
D.O.T. HAZARD NAME(49CFR 172.101): NONE
D.O.T. ID NO(49CFR 172.101): NONE
D.O.T. HAZARD CLASS(49CFR 172.101): NONE
RCRA HAZARD CLASS(40CFR 261)(IF DISCARDED): NONE
E.P.A. PRIORITY POLLUTANTS(40CFR 122.53): NONE
NFPA = NATIONAL FIRE PROTECTION ASSOCIATION - 704
HEALTH (NFPA): 1 FLAMMABILITY (NFPA): 1 REACTIVITY (NFPA): 0
CAS NO: MIXTURE DOW CORNING WARNING CODE: 76
GENERIC DESCRIPTION: SILICONE

SECTION II - HAZARDOUS INGREDIENT

NONE PRESENT % TLV (UNITS):

ONLY THOSE INGREDIENTS LISTED IN THIS SECTION HAVE BEEN DETERMINED TO BE HAZARDOUS AS DEFINED IN 29 CFR 1910.1200. AN INGREDIENT MARKED WITH AN ASTERISK(*) IS ALSO LISTED IN 29 CFR 1910.1200(D) #4 AS KNOWN OR SUSPECTED CARCINOGEN.

COMMENT: NONE.

DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

MATL NAME: MOLYKOTE(R) 33 GREASE - LIGHT

SECTION III - EFFECTS OF OVEREXPOSURE

EYES: MAY CAUSE TEMPORARY DISCOMFORT.

SKIN: SINGLE, PROLONGED EXPOSURE (HOURS) CAUSES NO KNOWN EFFECT.
SEVERAL REPEATED, PROLONGED EXPOSURES MAY CAUSE SLIGHT IRRITATION.

INHALATION: NO EFFECTS EXCEPT VERY SLIGHT IRRITATION OR PAIN TO THE
EYES OR RESPIRATORY PASSAGES.

ORAL: AMOUNTS TRANSFERRED TO THE MOUTH BY FINGERS, ETC., DURING
NORMAL OPERATIONS SHOULD NOT CAUSE INJURY.

COMMENT: NO KNOWN ADVERSE CHRONIC HEALTH EFFECTS, BUT UNNECESSARY
EXPOSURE TO ANY CHEMICAL SHOULD BE AVOIDED.
THIS PRODUCT, AS WITH ANY CHEMICAL, MAY ENHANCE ALLERGIC CONDITIONS ON CERTAIN
PEOPLE. WE DO NOT KNOW OF ANY MEDICAL CONDITIONS THAT MIGHT BE AGGRAVATED BY
EXPOSURE TO THIS PRODUCT.

SECTION IV - EMERGENCY AND FIRST AID PROCEDURES

EYES: FLUSH WITH WATER.

SKIN: WIPE OFF AND FLUSH WITH WATER.

INHALATION: NO PROBLEM.

ORAL: NO PROBLEM.

COMMENT: NONE.

SECTION V - FIRE AND EXPLOSION DATA

FLASH POINT (METHOD USED): OPEN CUP ABOVE 250°F/121°C

AUTOIGNITION: NOT DETERMINED.

FLAMMABILITY LIMITS IN AIR : LOWER:N.A. UPPER: N.A.

EXTINGUISHING MEDIA: WATER WATER FOG X CO2 X DRY CHEMICAL X FOAM X OTHER

SPECIAL FIRE FIGHTING PROCEDURES: SELF-CONTAINED BREATHING APPARATUS AND
PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE KNOWN TO DOW CORNING.

COMMENTS: N.A. - NOT APPLICABLE.

SECTION VI - PHYSICAL DATA

BOILING POINT(2 760 MM HG): ABOVE 300°F/149°C.

SPECIFIC GRAVITY (AT 77 DEG F/25 DEG C): 1.05

MELTING POINT: NOT APPLICABLE

VAPOR PRESSURE (AT 77 DEG F/25 DEG C): LESS THAN 5 MM.

VAPOR DENSITY (AIR = 1 AT 77 DEG F/25 DEG C): NOT APPLICABLE

PERCENT VOLATILE BY VOLUME (%): LESS THAN 5%

EVAPORATION RATE (ETHER = 1): LESS THAN 1

SOLUBILITY IN WATER(%): LESS THAN 0.1%

ODOR, APPEARANCE, COLOR: VERY LITTLE ODOR, GREASE, LIGHT BEIGE-TAN

NOTE: THE ABOVE INFORMATION IS NOT INTENDED FOR USE IN PREPARING PRODUCT
SPECIFICATIONS. CONTACT DOW CORNING BEFORE WRITING SPECIFICATIONS

DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

MATL NAME: MOLYKOTE(R) 33 GREASE - LIGHT

SECTION VII - REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY(MATERIAL TO AVOID): OXIDIZING MATERIAL CAN CAUSE A REACTION.

CONDITIONS TO AVOID: NOT APPLICABLE

HAZARDOUS DECOMPOSITION PRODUCTS: SILICON DIOXIDE, CARBON DIOXIDE, AND TRACES OF INCOMPLETELY BURNED CARBON PRODUCTS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: NOT APPLICABLE

COMMENTS: NONE.

SECTION VIII - SPILL, LEAK AND DISPOSAL PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: REMOVE PRODUCT AND USE ABSORBENT MATERIAL TO TAKE CARE OF ANY OIL-LIKE RESIDUES.

PROTECTIVE EQUIPMENT:

EYES: USE PROPER PROTECTION -- SAFETY GLASSES, AS A MINIMUM.

SKIN: WASHING AT MEALTIME AND END OF SHIFT IS ADEQUATE.

INHALATION: NO RESPIRATORY PROTECTION REQUIRED.

WASTE DISPOSAL METHOD: DOW CORNING SUGGESTS THAT ALL LOCAL, STATE AND FEDERAL REGULATIONS CONCERNING HEALTH AND POLLUTION BE REVIEWED TO DETERMINE APPROVED DISPOSAL PRODEURES. CONTACT DOW CORNING IF THERE ARE ANY DISPOSAL QUESTIONS.

D.O.T. (49CFR 171.8)/E.P.A. (40CFR 117) SPILL REPORTING INFORMATION

HAZARDOUS SUBSTANCE: NONE

REPORTABLE QUANTITY: NOT APPLICABLE

CONCENTRATION OF HAZARDOUS SUBSTANCE: NOT APPLICABLE

REPORTABLE QUANTITY OF PRODUCT: NOT APPLICABLE

COMMENTS: NONE.

SECTION IX - ROUTINE HANDLING PRECAUTIONS

PROTECTIVE EQUIPMENT:

EYES: USE PROPER PROTECTION -- SAFETY GLASSES, AS A MINIMUM.

SKIN *: WASHING AT MEALTIME AND END OF SHIFT IS ADEQUATE.

INHALATION: NO RESPIRATORY PROTECTION REQUIRED.

VENTILATION:

LOCAL EXHAUST: NONE

MECHANICAL (GENERAL): RECOMMENDED

SUITABLE RESPIRATOR: NONE SHOULD BE NEEDED.

THESE PRECAUTIONS ARE FOR ROOM TEMPERATURE HANDLING, USE AT ELEVATED TEMPERATURE MAY REQUIRE ADDED PRECAUTIONS.

* GOOD PRACTICE REQUIRES THAT GROSS AMOUNT OF ANY CHEMICAL BE REMOVED FROM THE SKIN AS SOON AS PRACTICAL, ESPECIALLY BEFORE EATING OR SMOKING.

COMMENTS: NONE

SECTION X - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: USE REASONABLE CARE AND CAUTION.

OTHER PRECAUTIONS: NONE KNOWN TO DOW CORNING.

COMMENTS: TRACES OF FORMALDEHYDE AND OTHER THERMAL DECOMPOSITION PRODUCTS MAY FORM AT TEMPERATURES ABOVE 150C IN THE PRESENCE OF AIR. PROVIDE ADEQUATE VENTILATION WHEN HANDLING AT ELEVATED TEMPERATURES.

DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

MATL NAME: MOLYKOTE(R) 33 GREASE - LIGHT

THESE DATA ARE OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EITHER EXPRESSED OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE.

PREPARED BY: JACK L. SHENEBERGER
LAST REVISION DATE: SEPTEMBER 27, 1985
PREVIOUS REVISION DATE: JANUARY 14, 1981
DATE: MAY 31, 1986

(R) INDICATES REGISTERED OR TRADEMARK OF THE DOW CORNING CORPORATION.